

# SUNITEC TFP200 8" Scarifier

# TFP200 SCARIFIER

2022 **NEW PRODUCT IMPROVEMENTS** 

### **NEW 2022 FEATURES**







Rear mounted starter box enclosure



Handle integrated start button



Tool & Vacuum System Compatible



# **NEW! 120V 1-PHASE TFP200 NOW AVAILABLE**

#### **EVERY TFP200 SCARIFIER INCLUDES** MOUNTED DRUM AND CUTTERS

**Max. Cutting Depth** 

1/8" per pass

**Cutting Width** 

۵II

#### **TFP200 Electric**

TFP200 Gas				
320.2012T Motor: 165CFM @ 90 PSI, 3.5 HP		99 lbs.		
TFP200 Pneumatic				
320.2406T	Motor: 400V, 50/60 Hz, 3-Ph, 3 HP	149 lbs.		
320.2404T	Motor: 230V, 50/60 Hz, 1-Ph, 3 HP	149 lbs.		
320.2342T	Motor: 120V, 50/60 Hz, 1-Ph, 1.5 HP	149 lbs.		

Motor: Honda GX160 Gas, 5.5 HP

Machine dimensions are 14"w x 35" l x 35" h.

# TYPICAL APPLICATIONS

- Remove and profile concrete
- Trip hazard removal
- Removal of paints, dirt and ice deposits
- Removal of roofing materials
- Removal of line markings
- Removal of coatings & scale from steel



**Use with Dust Control System** 

### DRUM OPTIONS



320.2000T

TCT Cutter **Drum** 

High performance concrete planing



Star Cutter **Drum** 

Paint & coatings



Beam Cutter **Drum** 

Light profiling



130 lbs.

Wire Brush **Drum** 

Light surface & steel finishing

CONTACT US FOR PRIVATE-BRANDED WRAP OPTIONS

Please contact CS United to find your local distributor: Call 800-700-5919 or 203-853-9522





# 8" Floor Scarifiers





## Level and profile concrete, as well as remove coatings, epoxies and more





CS Unitec's Trelawny™ Floor Scarifiers tackle the most demanding surface preparation and material removal jobs. The TFP200 is ideal for planing concrete and asphalt surfaces. With a purpose-built design and optimal weight distribution, the TFP200 scarifiers maintain high productivity with excellent maneuverability and reduced user fatigue.









# Electric 120V, 1-Ph 230V, 1-Ph 400V, 3-Ph

## **Benefits:**

High Durability: Rigid steel chassis, robust webbed drum assembly, impact-resistant, enclosed electronics

**Economical:** Pre-mounted hassle-free drums – ready to run! Engineered for continuous use, simple operation and low maintenance

Increased Safety: Hold-to-run switch, offset vacuum port Productivity & Versatility: 1/8" depth of cut, high production and removal rates, 6+ cutter options, quick-change drums

User Comfort: Comfort grips, easy access controls, increased leverage and maneuverability

**Accuracy:** Fine adjustment for precise depth control, cutting depth lock for consistency, compact design for tight spaces

#### Ideal for small to medium-sized jobs:

- Use on concrete, asphalt, stone, metal, steel and more
- Remove coatings, epoxies, paint, traffic/parking lot lines, thermoplastics, carpet adhesives, and more
- Level concrete, asphalt, and stone. Reduce sidewalk heaves/trip hazards and level high spots
- Roughen/plane concrete, asphalt and stone
- Create keyed, grooved profiles or non-slip surfaces
- Remove paint, rust, scale, and more

#### **TFP200 Scarifiers**

**Max. Cutting Depth** 

1/8" per pass

**Cutting Width** 

BII

TFP200 Electric

#### **Every TFP200 Scarifier includes** mounted drum and cutters

320.2342T	Motor: 120V, 50/60 Hz, 1-Ph, 1.5 HP 149		
320.2404T	Motor: 230V, 50/60 Hz, 1-Ph, 3 HP	149 lbs.	
320.2406T	Motor: 400V, 50/60 Hz, 3-Ph, 3 HP 149 lbs		
TFP200 Pneumatic			
320.2012T	20.2012T Motor: 165CFM @ 90 PSI, 3.5 HP 99 lbs		
TFP200 Gas			
320.2000T Motor: Honda GX160 Gas, 5.5 HP		130 lbs.	
Machine dimensions are 14"w x 35" l x 35" h.			

#### **TFP200 Cutters and Uses**

Wire Brushes	Beam Cutters*	Star Cutters*	TCT Cutters*	Milling Cutters (22mm)*	TCT Cutters (for grooving)*
	Individual Cutter/Spacer				
N/A	320.5120	320.3658	320.5500/ 320.4140	320.5600/ 320.4140	320.5500/ 320.4140
Cutters/Spacers Per Drum					
N/A	208 Pieces	208 Pieces	80/88 Pieces	24/72 Pieces	24/232 Pieces
Drum Assembly					
320.9620	320.1020SB	320.1020SS	320.1020ST	320.1020SM	320.002G

<sup>\*</sup> Beam, Star, Milling and TCT Cutters are compatible with other manufacturers' models.

Wire Brushes: finish cleaning and polishing on steel; removing light concrete deposit. Beam Cutters: light paint/corrosion removal, minimal damage to substrate.

Star Cutters: removal of mastics and rubberized coatings.


Tungsten Carbide-Tipped (TCT) Cutters: aggressive applications such as roughing concrete, heavy corrosion removal, and grooving roadways for non-slip surface. Milling Cutters: removal of plastic road markings without penetrating the surface.

Please contact CS Unitec to find your local distributor: Call 800-700-5919 or 203-853-9522





# SUNITEC 10" Floor Scarifiers





## Level and profile concrete, as well as remove coatings, epoxies and more

CS Unitec's Trelawny<sup>TM</sup> Floor Scarifiers tackle the most demanding surface preparation and material removal jobs. The TFP260 is ideal for planing large-area concrete and asphalt surfaces. With a purpose-built design and optimal weight distribution, the TFP260 scarifiers maintain high productivity with excellent maneuverability and reduced user fatigue.





High Durability: Rigid steel chassis, robust webbed drum assembly, impact-resistant, enclosed electronics

**Economical:** Pre-mounted hassle-free drums – ready to run! Engineered for continuous use, simple operation and low maintenance

Increased Safety: Hold-to-run switch, offset vacuum port **Productivity & Versatility:** 1/4" depth of cut, high production and removal rates, 5 cutter options, quick-change drums

User Comfort: Comfort grips, easy access controls, increased leverage and maneuverability

Accuracy: Fine adjustment for precise depth control, cutting depth lock for consistency, compact design for tight spaces

#### Ideal for medium to large-sized jobs:

- Use on concrete, asphalt, stone, metal, steel and more
- Remove coatings, epoxies, paint, traffic/parking lot lines, thermoplastics, carpet adhesives, and more
- Level concrete, asphalt, and stone. Reduce sidewalk heaves/trip hazards and level high spots
- Roughen/plane concrete, asphalt and stone
- Create keyed, grooved profiles or non-slip surfaces
- Remove paint, rust, scale, and more







#### **TFP260 Scarifiers**

Max. Cutting Depth

**Cutting Width** 

1/4" per pass

10<sup>"</sup>

#### **Every TFP260 Scarifier includes** mounted drum and cutters

#### **TFP260 Electric**

326.2006T Motor: 415V, 50/60 Hz, 3-Ph, 7.5 HP 408 lbs.				
TFP260 Gas				
326.2000T	Motor: Honda GX240 Gas, 8 HP	408 lbs.		

Machine dimensions are 17"w x 44" l x 45" h.

#### **TFP260 Cutters and Uses**

Beam Cutters	Star Cutters	TCT Cutters	Milling Cutters (16mm)	TCT Cutters (for grooving)	
Individual Cutter/Spacer					
326.5120	326.3658	320.7009/ 320.4160	320.5680	320.7009/ 320.4160	
Cutters/Spacers Per Drum					
332 Pieces	342 Pieces	123/129 Pieces	60 Pieces	36/224 Pieces	
Drum Assembly					
326.1016DB	326.1016DS	326.1016ST	326.1016DM	326.1016GT	

Beam Cutters: light paint/corrosion removal, minimal damage to substrate.

Star Cutters: removal of mastics and rubberized coatings.

Tungsten Carbide-Tipped (TCT) Cutters: aggressive applications such as roughing concrete, heavy corrosion removal, and grooving roadways for non-slip surface. Milling Cutters: removal of plastic road markings without penetrating the surface.

Please contact CS United to find your local distributor: Call 800-700-5919 or 203-853-9522

